NSN 3020-00-905-1902

Spur Gear - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/3020-00-905-1902 |
|--|
| Body Style: |
| Plain, solid |
| Attachment Method: |
| Mounting hole |
| Pitch Diameter: |
| 2.2500 inches |
| Teeth Quantity: |
| 72 |
| Mounting Hole Thread Series Designator: |
| Unc transversely through hub, first end |
| Mounting Hole Thready Qty Per Inch (tpi): |
| 32 transversely through hub, first end |
| Mounting Hole Type And Quantity: |
| 1 threaded transversely through hub, first end |
| Nominallength: |
| 0.563 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.188 inches first end |
| Face Width: |
| 0.375 inches |
| Bore Diameter: |
| 0.375 inches both ends |
| Hub Diameter: |
| 0.750 inches first end |
| Material: |
| Steel comp 303 |
| Material Specification: |
| Qq-s-763, class 303, cond a federal specification single material response |
| Surface Treatment: |
| Passivate |
| Style Designator: |
| Protruding hub |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 3020-00-905-1902 Spur Gear - Page 2 of 2

Fiig: A27300

