

View Online at <https://aerobasegroup.com/nsn/3020-00-905-2651>

Body Style:

Webbed, offset, solid

Attachment Method:

Mounting hole

Pitch Diameter:

Between 6.7490 inches and 6.7500 inches

Teeth Quantity:

324

Bore Style:

W/counterbore first end

Backlash Designation:

Grade c

Mounting Hole Type And Quantity:

10 plain axially through hub, first end

Outside Diameter:

6.792 inches

Tooth Form:

Standard

Pressure Angle:

20.0000 degrees

Distance Between Body Face And Protruding Hub End:

0.312 inches first end

Face Width:

0.188 inches

Bore Diameter:

5.750 inches both ends

Counterbore Depth:

0.375 inches first end

Counterbore Diameter:

6.250 inches first end

Hub Style Designator:

1 step first end

End Length:

0.250 inches first end

Precision Classification:

Quality number 10

End Diameter:

6.500 inches first end

First Step Length:

0.062 inches first end

First Step Diameter:

6.625 inches first end

Mounting Hole Diameter:

0.101 inches axially through hub, first end

Bolt Hole Circle Diameter:

6.000 inches axially through hub, first end

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-225/6, t4 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.