

View Online at <https://aerobasegroup.com/nsn/3020-00-905-2651>

**Body Style:**

Webbed, offset, solid

**Attachment Method:**

Mounting hole

**Pitch Diameter:**

Between 6.7490 inches and 6.7500 inches

**Teeth Quantity:**

324

**Bore Style:**

W/counterbore first end

**Backlash Designation:**

Grade c

**Mounting Hole Type And Quantity:**

10 plain axially through hub, first end

**Outside Diameter:**

6.792 inches

**Tooth Form:**

Standard

**Pressure Angle:**

20.0000 degrees

**Distance Between Body Face And Protruding Hub End:**

0.312 inches first end

**Face Width:**

0.188 inches

**Bore Diameter:**

5.750 inches both ends

**Counterbore Depth:**

0.375 inches first end

**Counterbore Diameter:**

6.250 inches first end

**Hub Style Designator:**

1 step first end

**End Length:**

0.250 inches first end

**Precision Classification:**

Quality number 10

**End Diameter:**

6.500 inches first end

**First Step Length:**

0.062 inches first end

**First Step Diameter:**

6.625 inches first end

**Mounting Hole Diameter:**

0.101 inches axially through hub, first end

**Bolt Hole Circle Diameter:**

6.000 inches axially through hub, first end

**Material:**

Aluminum alloy 2024

**Material Specification:**

Qq-a-225/6, t4 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625 military specification single treatment response

**Style Designator:**

Protruding hub

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A27300

**Mil-std (military Standard):**

Mil-a-8625 spec.