## NSN 3020-00-905-3124

Spur Gear - Page 1 of 2

**Body Style:** 

Mounting hole

Pitch Diameter:

1.4580 inches

Teeth Quantity:

**Bore Style:** 

10a w/ keyway both ends

**Mounting Hole Type And Quantity:** 

35

Webbed, offset, solid **Attachment Method:** 



View Online at https://aerobasegroup.com/nsn/3020-00-905-3124

4 plain axially through body, first end
Outside Diameter:
1.500 inches
Nominallength:
0.610 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.314 inches first end
Body Recess Depth:
0.150 inches second end
Face Width:
0.296 inches
Bore Diameter:
0.502 inches both ends
Keyway Width:
0.200 inches both ends
Distance From Bore Center To Keyway Bottom:
0.323 inches both ends
Hub Style Designator:
Split first end
Hub Diameter:
0.707 inches first end
Mounting Hole Diameter:
0.031 inches axially through body, first end
Bolt Hole Circle Diameter:
0.920 inches axially through body, first end
Special Features:
Mtg holes spaced 90 degrees apart starting in line w/keyway; 2 circumferential grooves in bore

## NSN 3020-00-905-3124

Spur Gear - Page 2 of 2

**Fiig:** A27300



Material:
Steel comp 303
Material Specification:
Qq-s-764, type 303, cond a federal specification single material response
Surface Treatment:
Passivate
Style Designator:
Protruding hub, recessed body
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No