## NSN 3020-00-905-3124

Spur Gear - Page 1 of 2

**Body Style:** 

Mounting hole

Pitch Diameter:

1.4580 inches

Teeth Quantity:

**Bore Style:** 

10a w/ keyway both ends

**Mounting Hole Type And Quantity:** 

35

Webbed, offset, solid **Attachment Method:** 



View Online at https://aerobasegroup.com/nsn/3020-00-905-3124

| 4 plain axially through body, first end  |
|--|
| Outside Diameter:  |
| 1.500 inches   |
| Nominallength:   |
| 0.610 inches   |
| Tooth Form:  |
| Standard   |
| Pressure Angle:  |
| 20.0000 degrees  |
| Distance Between Body Face And Protruding Hub End:   |
| 0.314 inches first end   |
| Body Recess Depth:   |
| 0.150 inches second end  |
| Face Width:  |
| 0.296 inches   |
| Bore Diameter:   |
| 0.502 inches both ends   |
| Keyway Width:  |
| 0.200 inches both ends   |
| Distance From Bore Center To Keyway Bottom:  |
| 0.323 inches both ends   |
| Hub Style Designator:  |
| Split first end  |
| Hub Diameter:  |
| 0.707 inches first end   |
| Mounting Hole Diameter:  |
| 0.031 inches axially through body, first end   |
| Bolt Hole Circle Diameter:   |
| 0.920 inches axially through body, first end   |
| Special Features:  |
| Mtg holes spaced 90 degrees apart starting in line w/keyway; 2 circumferential grooves in bore |
|  |
|  |
|  |

## NSN 3020-00-905-3124

Spur Gear - Page 2 of 2

**Fiig:** A27300



| Material:   |
|---|
| Steel comp 303  |
| Material Specification:   |
| Qq-s-764, type 303, cond a federal specification single material response |
| Surface Treatment:  |
| Passivate   |
| Style Designator:   |
| Protruding hub, recessed body   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |