NSN 3020-00-907-8576

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-907-8576 **Attachment Method:** Mounting hole Pitch Diameter: 0.7500 inches **Teeth Quantity:** 90 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unf transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 80 transversely through hub, first end **Mounting Hole Thread Size:** 0.060 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 2 threaded transversely through hub, first end **Outside Diameter:** 0.7660 inches Nominallength: 0.223 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.114 inches first end **Face Width:** 0.109 inches **Bore Diameter:** 0.090 inches both ends **Hub Style Designator:** Plain first end **Hub Diameter:** 0.250 inches first end Material: Steel comp 303 **Material Specification:** Qq-s-763, class302 federal specification single material response **Surface Treatment: Passivate**

Style Designator: Protruding hub

NSN 3020-00-907-8576

Spur Antibacklash Gear - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300