## NSN 3020-00-907-8578

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-907-8578 **Attachment Method:** Mounting hole Pitch Diameter: 0.5420 inches **Teeth Quantity:** 65 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unf transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 80 transversely through hub, first end **Mounting Hole Thread Size:** 0.060 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 2 threaded transversely through hub, first end **Outside Diameter:** 0.5540 inches Nominallength: 0.218 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.125 inches first end **Face Width:** 0.093 inches **Bore Diameter:** 0.101 inches both ends **Hub Style Designator:** Plain first end **Hub Diameter:** 0.250 inches first end Material: Steel comp 303 **Material Specification:** Qq-s-763, class303 federal specification single material response **Surface Treatment: Passivate Style Designator:** 

Protruding hub

## NSN 3020-00-907-8578

Spur Antibacklash Gear - Page 2 of 2



Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A27300