NSN 3020-00-907-8580

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-907-8580

| Attachment Method: |
|---|
| Mounting hole |
| Pitch Diameter: |
| 0.6660 inches |
| Teeth Quantity: |
| 80 |
| Bore Style: |
| Plain both ends |
| Mounting Hole Thread Series Designator: |
| Unf transversely through hub, first end |
| Mounting Hole Thready Qty Per Inch (tpi): |
| 80 transversely through hub, first end |
| Mounting Hole Thread Size: |
| 0.060 inches transversely through hub, first end |
| Mounting Hole Type And Quantity: |
| 1 threaded transversely through hub, first end |
| Outside Diameter: |
| 0.6830 inches |
| Nominallength: |
| 0.218 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.125 inches first end |
| Face Width: |
| 0.093 inches |
| Bore Diameter: |
| 0.101 inches both ends |
| Hub Style Designator: |
| Plain first end |
| Hub Diameter: |
| 0.250 inches first end |
| Material: |
| Steel comp 303 |
| Material Specification: |
| Qq-s-763, class303 federal specification single material response |
| Surface Treatment: |
| Passivate |
| Style Designator: |
| Protruding hub |
| |

NSN 3020-00-907-8580

Spur Antibacklash Gear - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A27300

