

View Online at <https://aerobasegroup.com/nsn/3020-00-908-0947>

Outside Diameter:

Between 0.999 inches and 1.001 inches

Overall Length:

0.718 inches

Thread Size:

No. 6 /0.138/-32

Bore Diameter:

0.375 inches

Bore Length:

0.718 inches

Securing Hole Quantity:

2

Material And Location:

Steel, qq-s-763, class 310

Face Width:

0.312 inches

Design Form:

Plain

Bore Type:

Straight

Bearings:

Not included

Counterbore Feature:

Not included

Hole Location:

90 degrees apart 0.218 in. From hub end

Keying Facility:

Not included

Securing Method:

Threaded hole

Split Hub Feature:

Not included

Lightening Hole:

Not included

Integral Cooling Vane:

Not included

Crown Face:

Included

Rim Type:

Solid

Bore Feature:

Included

Protruding Hub Characteristic:

Stepped

Securing Location:

Aa end

Hub End Outside Diameter And Location:

0.500 inches aa end

Distance From Outside Flange/rim To Hub End And Location:

0.406 inches aa end

First Step Face Largest Diameter And Location:

0.625 inches both ends

First Step Length And Location:

0.032 inches both ends

Surface Treatment:

Passivate

Style Designator:

Plain

Surface Treatment:

Passivated

Reference Number Differentiating Characteristics:

Mil-q-21549b-sp24-1

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T353-a

Mil-std (military Standard):

Mil-q-21549 spec.