NSN 3020-00-909-2651

Spur Gear - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/3020-00-909-2651

| Plain, solid |
|---|
| Attachment Method: |
| Mounting hole |
| Pitch Diameter: |
| 1.2187 inches |
| Teeth Quantity: |
| 78 |
| Bore Style: |
| Plain both ends |
| Mounting Hole Type And Quantity: |
| 1 plain axially through body, first end and 1 plain axially through body, first end |
| Outside Diameter: |
| 1.2500 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.3000 inches first end |
| Face Width: |
| 0.120 inches |
| Bore Diameter: |
| 0.2507 inches both ends |
| Hub Style Designator: |
| 2 steps first end |
| End Length: |
| 0.2000 inches first end |
| Precision Classification: |
| Quality number 10 |
| End Diameter: |
| 0.3630 inches first end |
| First Step Length: |
| 0.0550 inches first end |
| First Step Diameter: |
| 0.4320 inches first end |
| Second Step Length: |
| 0.0450 inches first end |
| Second Step Diameter: |
| 0.0550 inches first end |
| Mounting Hole Diameter: |
| 0.036 inches axially through body, first end and 0.062 inches axially through body, first |
| |

end

NSN 3020-00-909-2651

Spur Gear - Page 2 of 2



Bolt Hole Circle Diameter: 0.640 inches axially through body, first end Material: Copper alloy hub Material Specification: Qq-a-268, t4 federal specification single material response body Style Designator: Protruding hub Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fiig:

Mil-std (military Standard): Mil-b-5687 spec.

A27300