NSN 3020-00-912-8457

Spur Gear - Page 1 of 2





Body Style: Plain, solid

Attachment Method:

Mounting hole

Pitch Diameter:

Between 1.4990 inches and 1.5000 inches

Teeth Quantity:

36

Bore Style:

Plain both ends

Backlash Designation:

Grade c

Mounting Hole Thread Series Designator:

Unc transversely through hub, first end

Mounting Hole Thready Qty Per Inch (tpi):

32 transversely through hub, first end

Mounting Hole Thread Size:

0.138 inches transversely through hub, first end

Mounting Hole Type And Quantity:

2 threaded transversely through hub, first end

Outside Diameter:

1.582 inches

Nominallength:

0.437 inches

Tooth Form:

Standard

Pressure Angle:

20.0000 degrees

Distance Between Body Face And Protruding Hub End:

0.250 inches first end

Face Width:

0.187 inches

Bore Diameter:

0.250 inches both ends

Hub Style Designator:

Pinned first end

Hub Diameter:

0.500 inches first end

Precision Classification:

Quality number 10

Special Features:

Mtg holes 90 degs apart

NSN 3020-00-912-8457

Spur Gear - Page 2 of 2



Material:

Steel comp 303

Material Specification:

Qq-s-764, type 303, cond a federal specification single material response

Surface Treatment:

Passivate

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300