NSN 3020-00-913-1216

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-913-1216

Body Style: Webbed, offset, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 0.5625 inches **Teeth Quantity:** 54 **Bore Style:** Plain both ends **Backlash Designation:** Grade b Mounting Hole Thread Series Designator: Unc transversely through hub, first end Mounting Hole Thread Size: 0.086 inches transversely through hub, first end Mounting Hole Type And Quantity: 2 threaded transversely through hub, first end **Outside Diameter:** 0.583 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.140 inches first end Face Width: 0.062 inches **Bore Diameter:** 0.125 inches both ends Hub Style Designator: Plain first end **Hub Diameter:** 0.343 inches first end **Precision Classification:** Quality number 10 First Groove Width: 0.029 inches second end First Groove Diameter: 0.188 inches second end **Distance From End To First Groove:**

0.025 inches second end

NSN 3020-00-913-1216

Spur Gear - Page 2 of 2



Mounting Hole Diameter:

0.037 inches axially through body, first end

Material:

Steel

Material Specification:

66, aisi 303/sae 30303 federal standard single material response

Style Designator:

Protruding hubs

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300