NSN 3020-00-913-1216

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-913-1216

Body Style:
Webbed, offset, solid
Attachment Method:
Mounting hole
Pitch Diameter:
0.5625 inches
Teeth Quantity:
54
Bore Style:
Plain both ends
Backlash Designation:
Grade b
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thread Size:
0.086 inches transversely through hub, first end
Mounting Hole Type And Quantity:
2 threaded transversely through hub, first end
Outside Diameter:
0.583 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.140 inches first end
Face Width:
0.062 inches
Bore Diameter:
0.125 inches both ends
Hub Style Designator:
Plain first end
Hub Diameter:
0.343 inches first end
Precision Classification:
Quality number 10
First Groove Width:
0.029 inches second end
First Groove Diameter:
0.188 inches second end
Distance From End To First Groove:

0.025 inches second end

NSN 3020-00-913-1216

Spur Gear - Page 2 of 2

No Fiig: A27300



Mounting Hole Diameter: 0.037 inches axially through body, first end Material: Steel Material Specification: 66, aisi 303/sae 30303 federal standard single material response Style Designator: Protruding hubs Shelf Life: N/a Unit Of Measure: - Demilitarization: