NSN 3020-00-914-3721

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-914-3721

| Body Style: |
|--|
| Plain, solid |
| Attachment Method: |
| Mounting hole |
| Pitch Diameter: |
| 0.7291 inches |
| Teeth Quantity: |
| 35 |
| Bore Style: |
| Plain both ends |
| Backlash Designation: |
| Grade c |
| Mounting Hole Type And Quantity: |
| 2 plain axially through body, first end |
| Outside Diameter: |
| 0.7708 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 14.5000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.2810 inches first end |
| Body Recess Depth: |
| 0.1000 inches second end |
| Face Width: |
| 0.250 inches |
| Bore Diameter: |
| 0.2405 inches both ends |
| Hub Style Designator: |
| Plain first end |
| Hub Diameter: |
| 0.6250 inches first end |
| Precision Classification: |
| Quality number 10 |
| Mounting Hole Diameter: |
| 0.120 inches axially through body, first end |
| Bolt Hole Circle Diameter: |
| 0.437 inches axially through body, first end |
| Material: |
| Steel comp 416 |
| Material Specification: |
| Og-s-764 cond a federal specification single material response |

NSN 3020-00-914-3721

Spur Gear - Page 2 of 2



Passivate

Style Designator:

Protruding hub, recessed body

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300