## NSN 3020-00-916-0069

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-916-0069

De de Otele
Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
1.1250 inches
Teeth Quantity:
135
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
56 transversely through hub, first end
Mounting Hole Thread Size:
0.086 inches transversely through hub, first end
Mounting Hole Type And Quantity:
2 plain transversely through hub, first end and 1 threaded transversely through hub, first end
Outside Diameter:
1.141 inches
Nominallength:
0.200 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.145 inches first end
Face Width:
0.055 inches
Bore Diameter:
0.125 inches both ends
Hub Style Designator:
Pinned first end
Hub Diameter:
0.260 inches first end
Precision Classification:
Quality number 12
Mounting Hole Diameter:
0.052 inches transversely through hub, first end
Material:

Aluminum alloy 2024

## NSN 3020-00-916-0069

Spur Gear - Page 2 of 2



Material	Specific	cation:

Qq-a-225/6, t351 federal specification single material response

**Surface Treatment:** 

Anodize

**Style Designator:** 

Protruding hub

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A27300