NSN 3020-00-916-0070

Spur Gear Sector - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/3020-00-916-0070

Attackment Method
Attachment Method:
Mounting hole
Teeth Quantity:
110
Bore Style:
Plain both ends
Pitch Radius:
0.45835 inches
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
56 transversely through hub, first end
Mounting Hole Thread Size:
0.086 inches transversely through hub, first end
Mounting Hole Type And Quantity:
1 threaded transversely through hub, first end and 2 plain transversely through hub, first end
Nominallength:
0.250 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.1600 inches first end
Face Width:
0.090 inches
Bore Diameter:
0.124 inches both ends
Hub Style Designator:
Plain first end
Hub Diameter:
0.2550 inches first end
Outside Radius:
0.4663 inches
Precision Classification:
Quality number 12
Arc Length:
0.4950 inches
Mounting Hole Diameter:
0.052 inches transversely through hub, first end
Material:
Steel comp 303s

NSN 3020-00-916-0070

Spur Gear Sector - Page 2 of 2



Material Specification:

Mil-s-7720 military specification single material response

Surface Treatment:

Passivate or oxide

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A27300

Mil-std (military Standard):

Mil-s-7720 spec.