NSN 3020-00-916-0076

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-916-0076

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
0.9167 inches
Teeth Quantity:
88
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
56 transversely through hub, first end
Mounting Hole Thread Size:
0.086 inches transversely through hub, first end
Mounting Hole Type And Quantity:
2 plain transversely through hub, first end and 1 threaded transversely through hub, first end
Outside Diameter:
0.937 inches
Nominallength:
0.281 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.188 inches first end
Face Width:
0.093 inches
Bore Diameter:
0.125 inches both ends
Hub Style Designator:
Pinned first end
Hub Diameter:
0.255 inches first end
Precision Classification:
Quality number 12
Mounting Hole Diameter:
0.052 inches transversely through hub, first end
Material:

Aluminum alloy 2024

NSN 3020-00-916-0076

Spur Gear - Page 2 of 2



Material Specification:

Qq-a-225/6, t351 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.