## NSN 3020-00-917-4048

Spur Gear - Page 1 of 2

Protruding hubs



View Online at https://aerobasegroup.com/nsn/3020-00-917-4048 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 2.2708 inches **Teeth Quantity:** 109 **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 32 transversely through hub, first end **Hardness Rating:** 89.0 rockwell b and 94.0 rockwell b **Mounting Hole Type And Quantity:** 2 threaded transversely through hub, first end Nominallength: 0.531 inches **Tooth Form:** Standard **Pressure Angle:** 14.5000 degrees **Distance Between Body Face And Protruding Hub End:** 0.290 inches first end **Face Width:** 0.094 inches **Bore Diameter:** 0.250 inches both ends **End Length:** 0.031 inches second end **Precision Classification:** Quality number 10 or quality number 11 First Step Diameter: 0.500 inches second end Material: Steel comp 416 **Material Specification:** Qq-s-764, type 416 cond a federal specification single material response **Surface Treatment: Passivate Style Designator:** 

## NSN 3020-00-917-4048

Spur Gear - Page 2 of 2



		ife:	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A27300