NSN 3020-00-917-7652

Flat Pulley - Page 1 of 2

Securing Method:

Split Hub Feature:

Drilled hole

Not included



View Online at https://aerobasegroup.com/nsn/3020-00-917-7652 **Outside Diameter:** 0.0250 inches **Overall Length:** 0.220 inches **Bolt Circle Diameter:** 0.312 inches **Outside Diameter:** 0.375 inches **Thread Size:** 0-80 **Bore Diameter:** Between 0.094 inches and 0.095 inches **Bore Length:** 0.220 inches Flange Width: 0.020 inches **Drilled Hole Diameter:** 0.018 inches Flange Quantity: **Securing Hole Quantity:** 3 **Material And Location:** Aluminum alloy, qq-a-225/6, alloy 2024, t4 **Face Width:** 0.082 inches **Design Form:** Plain **Bore Type:** Straight Bearings: Not included **Counterbore Feature:** Not included **Hole Location:** 2 holes 0.074 in. From pulley face spaced 90 degrees apart, 1 hole on outside flange **Keying Facility:** Not included

NSN 3020-00-917-7652 Flat Pulley - Page 2 of 2



Lightening Hole:
Not included
Integral Cooling Vane:
Not included
Crown Face:
Not included
Rim Type:
Solid
Flange Location:
Outside
Bore Feature:
Included
Securing Location:
Pulley surface
Hub End Outside Diameter And Location:
0.220 inches aa end
Distance From Outside Flange/rim To Hub End And Location:
0.138 inches aa end
Surface Treatment:
Anodize
Style Designator:
Plain
Surface Treatment:
Anodized
Fsc Application Data:
Display set, navigational, airborne
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T353-a