

NSN 3020-00-919-5028 Sprocket Wheel - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-919-5028 **Outside Diameter: 6.227 inches Overall Length:** 1.875 inches **Keyway Width:** 0.313 inches **Thread Size:** 5/8 in.-11 **Bore Diameter:** Between 2.750 inches and 2.753 inches **Bore Length:** 1.875 inches **Distance From Center Of Bore To Bottom Of Keyway:** 1.688 inches Pitch Diameter: 5.617 inches **Securing Hole Quantity: Furnished Items And Quantity:** Setscrew, 1 Face Width: 0.692 inches Guide: Not included **Design Form:** Plain

Bore Type:

Straight

Counterbore Feature:

Not included

Hole Location:

Located 90 degrees from keyway

Keying Facility:

Included

Keying Facility Type:

Keyway

Securing Method:

Threaded hole

Lightening Hole:

Not included

Protruding Hub Characteristic:

Plain

NSN 3020-00-919-5028 Sprocket Wheel - Page 2 of 2



| Securing Location: |
|---|
| Aa end |
| Belt/chain/film Size For Which Designed: |
| Roller chain |
| Roller Chain Pitch Type For Which Designed: |
| Single pitch |
| Teeth Row Quantity: |
| 1 |
| Teeth Quantity Per Row: |
| 14 |
| Asa Standard Chain Number: |
| 100 |
| Hardness Rating Test Method: |
| Not rated |
| Bore Bearing: |
| Not included |
| Hub External Keyway: |
| Not included |
| Tooth Pitch: |
| 1.250 inches |
| Hub End Outside Diameter And Location: |
| 4.188 inches aa end |
| Distance From Outside Flange/rim To Hub End And Location: |
| 1.183 inches aa end |
| Material: |
| Steel |
| Material: |
| Steel |
| Quantity: |
| 1 |
| Style Designator: |
| Plain |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Filg: |
| T353-c |