## NSN 3020-00-922-0086

Spur Gear - Page 1 of 2





Body Style:

Plain, solid

**Attachment Method:** 

Mounting hole

Pitch Diameter:

Between 3.7490 inches and 3.7500 inches

**Teeth Quantity:** 

120

Bore Style:

Plain both ends

**Backlash Designation:** 

Grade c

Mounting Hole Type And Quantity:

2 plain transversely through hub, first end

Outside Diameter:

3.812 inches

Tooth Form:

Standard

Pressure Angle:

20.0000 degrees

Distance Between Body Face And Protruding Hub End:

0.418 inches first end

Face Width:

0.312 inches

Bore Diameter:

2.952 inches both ends

Hub Style Designator:

1 step first end

End Length:

0.105 inches first end

**Precision Classification:** 

Quality number 10

End Diameter:

3.250 inches first end

First Step Length:

0.313 inches first end

First Step Diameter:

3.500 inches first end

Mounting Hole Diameter:

0.078 inches transversely through hub, first end

**Special Features:** 

Mtg holes centered 0.250 in. From end of hub 90 degrees apart

# NSN 3020-00-922-0086

Spur Gear - Page 2 of 2



## Material:

Steel comp 303

## **Material Specification:**

Qq-s-764, type 303, cond a federal specification single material response

#### Surface Treatment:

Passivate

## Surface Treatment Specification:

Mil-f-14072, finish e300 military specification single treatment response

## Style Designator:

Protruding hub

Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A27300

## Mil-std (military Standard):

Mil-f-14072 spec.