NSN 3020-00-922-4593

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-922-4593

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
0.9500 inches
Teeth Quantity:
76
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
56 transversely through hub, first end
Mounting Hole Thread Size:
0.086 inches transversely through hub, first end
Mounting Hole Type And Quantity:
1 threaded transversely through hub, first end
Outside Diameter:
0.975 inches
Nominallength:
0.306 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.244 inches first end
Face Width:
0.062 inches
Bore Diameter:
0.120 inches both ends
Hub Style Designator:
1 step first end
End Diameter:
0.218 inches first end
First Step Length:
0.119 inches first end
First Step Diameter:
0.625 inches first end
Second Sten Length:

0.125 inches first end

NSN 3020-00-922-4593

Spur Gear - Page 2 of 2



S	pe	cia	al F	-ea	ıtu	re	S
---	----	-----	------	-----	-----	----	---

 $W/0.032 \ in. \ Diameter \ hole, \ 0.093 \ in. \ Deep, \ countersunk \ 90 \ degrees \ to \ 0.062 \ in. \ Dia., \ located \ 0.215 \ in. \ From \ center \ of \ bore, \ w/o.500 \ in. \ Dia.$

By 0.030 in. Lg undercut in step at right angle to bore

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-225/8, t651 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Style Designator:

Protruding hub

•

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.