# NSN 3020-00-922-4595

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-922-4595

#### **Body Style:**

Plain, solid

**Pitch Diameter:** 

0.9500 inches

# Teeth Quantity:

76

#### Bore Style:

Plain both ends

#### Backlash Designation:

Grade c

### **Outside Diameter:**

0.975 inches

#### Tooth Form:

Standard

#### **Pressure Angle:**

2.0000 degrees

#### Distance Between Body Face And Protruding Hub End:

0.244 inches first end

#### Face Width:

0.062 inches

#### Bore Diameter:

0.090 inches both ends

#### Hub Style Designator:

Pinned second end

#### Hub Diameter:

0.375 inches second end

#### **Precision Classification:**

Quality number 10 or quality number 11

#### First Groove Width:

0.017 inches first end

#### First Groove Diameter:

0.203 inches first end

#### **Distance From End To First Groove:**

0.037 inches first end

#### **Special Features:**

Counterbore 90 degrees to 0.062 in.Dia.Located 0.215 in.From center of bore with 0.500 in. Diameter by 0.030 in. Lg undercut in step at

right angle to bore

#### Material:

Aluminum alloy 6061

## Material Specification:

Qq-a-225/8, t6 federal specification single material response

#### Surface Treatment:

Anodize

# NSN 3020-00-922-4595

Spur Gear - Page 2 of 2



## Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

## Style Designator:

Protruding hubs

Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.