NSN 3020-00-922-4645

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-922-4645

Body Style: Plain, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 0.7500 inches **Teeth Quantity:** 54 **Bore Style:** Plain both ends Mounting Hole Thread Series Designator: Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 56 transversely through hub, first end Mounting Hole Thread Size: 0.086 inches transversely through hub, first end Mounting Hole Type And Quantity: 2 threaded transversely through hub, first end **Outside Diameter:** 0.777 inches Nominallength: 0.343 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.156 inches first end Face Width: 0.062 inches **Bore Diameter:** 0.090 inches both ends Hub Style Designator: Plain second end **Hub Diameter:** 0.218 inches both ends First Groove Width: 0.018 inches first end First Groove Diameter: 0.205 inches first end **Distance From End To First Groove:** 0.040 inches first end

NSN 3020-00-922-4645

Spur Gear - Page 2 of 2



Material:

Aluminum alloy 6061

Material Specification:

Qq-a-225/8, t6 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Style Designator:

Protruding hubs

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.