## NSN 3020-00-922-4645



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-922-4645 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 0.7500 inches **Teeth Quantity:** 54 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 56 transversely through hub, first end **Mounting Hole Thread Size:** 0.086 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 2 threaded transversely through hub, first end **Outside Diameter:** 0.777 inches Nominallength: 0.343 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.156 inches first end **Face Width:** 0.062 inches **Bore Diameter:** 0.090 inches both ends **Hub Style Designator:** Plain second end **Hub Diameter:** 0.218 inches both ends First Groove Width: 0.018 inches first end

Distance From End To First Groove:

**First Groove Diameter:** 0.205 inches first end

0.040 inches first end

## NSN 3020-00-922-4645

Spur Gear - Page 2 of 2



Material:
Aluminum alloy 6061
Material Specification:
Qq-a-225/8, t6 federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625 military specification single treatment response
Style Designator:
Protruding hubs
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300
Mil-std (military Standard):
Mil-a-8625 spec.