NSN 3020-00-922-8017



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-922-8017 **Body Style:** Plain, solid **Attachment Method:** Mounting hole **End Application:** ARMA-ME-NTS-UBSY Pitch Diameter: 0.8750 inches **Teeth Quantity:** 28 **Bore Style:** Plain both ends **Backlash Designation:** Grade c **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end **Hardness Rating:** 38.0 rockwell c and 45.0 rockwell c **Mounting Hole Thread Size:** 0.138 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 plain transversely through hub, first end and 1 threaded transversely through hub, first end **Outside Diameter:** 0.937 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.297 inches first end **Body Recess Depth:** 0.265 inches counterbore, first end **Face Width:** 0.265 inches **Bore Diameter:** 0.375 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.562 inches first end

Quality number 9

Precision Classification:

NSN 3020-00-922-8017

Spur Gear - Page 2 of 2



Mounting Hole Diameter:

0.124 inches transversely through hub, first end

Material:

Steel

Surface Treatment:

Passivate

Style Designator:

Protruding hub, recessed body

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300