NSN 3020-00-923-8492

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-923-8492 **Outside Diameter:** 0.529 inches **Overall Length:** 0.343 inches **Thread Size:** 0.112-40 **Bore Diameter:** 0.187 inches **Bore Length:** 0.343 inches **Drilled Hole Diameter:** 0.040 inches Pitch Diameter: 0.477 inches **Securing Hole Quantity: Furnished Items And Quantity:** Setscrew 1 Face Width: 0.125 inches Guide: Not included **Design Form:** Plain **Bore Type:** Straight **Counterbore Feature:** Not included **Hole Location:** Located on hub portion of sprocked wheel between hub end and face, and located 90 degrees from thd hole **Keying Facility:** Not included **Securing Method:** Threaded hole and **Lightening Hole:** Not included **Protruding Hub Characteristic:** Plain **Securing Location:**

Roller chain

Belt/chain/film Size For Which Designed:

NSN 3020-00-923-8492 Sprocket Wheel - Page 2 of 2



Roller Chain Pitch Type For Which Designed:
Single pitch
Teeth Row Quantity:
1
Teeth Quantity Per Row:
10
Hardness Rating Test Method:
Not rated
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
0.148 inches
Hub End Outside Diameter And Location:
0.375 inches both ends
Distance From Outside Flange/rim To Hub End And Location:
0.218 inches both ends
Material:
Steel, mil-s-7720, comp 303s or steel, mil-s-7720, comp 303se
Material:
Steel comp 303 or steel comp 303se
Material Specification:
Mil-s-7720, comp 303s military specification 1st material response and mil-s-7720, comp 303se military specification 2nd material response
Surface Treatment:
Passivate
Style Designator:
Plain
Surface Treatment:
Passivated
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
T353-c
Mil-std (military Standard):
Mil-s-7720 spec.