NSN 3020-00-925-2247

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-925-2247 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 0.5476 inches **Teeth Quantity:** 26 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 32 transversely through hub, first end **Mounting Hole Thread Size:** 0.138 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 0.582 inches Nominallength: 0.690 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.190 inches first end **Face Width:** 0.500 inches **Bore Diameter:** 0.250 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.406 inches first end **Precision Classification:** Quality number 12 Material: Steel comp 303se **Material Specification:**

Mil-s-7720, comp 303se military specification single material response

NSN 3020-00-925-2247

Spur Gear - Page 2 of 2

Mil-std (military Standard):

Mil-s-7720 spec.



| Surface Treatment: |
|--|
| Chromium |
| Surface Treatment Specification: |
| Mil-f-14072 military specification single treatment response |
| Style Designator: |
| Protruding hub |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A27300 |