NSN 3020-00-925-5698

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-925-5698

| Body Style: |
|--|
| Webbed, solid |
| Pitch Diameter: |
| 2.7500 inches |
| Teeth Quantity: |
| 44 |
| Bore Style: |
| 10a w/ keyway both ends |
| Hardness Rating: |
| 58.0 rockwell c hub and 63.0 rockwell c hub |
| Outside Diameter: |
| 2.875 inches |
| Nominallength: |
| 1.417 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.411 inches both ends |
| Face Width: |
| 0.585 inches |
| Bore Diameter: |
| 0.683 inches both ends |
| Keyway Width: |
| 0.192 inches both ends |
| Distance From Bore Center To Keyway Bottom: |
| 0.393 inches both ends |
| Hub Style Designator: |
| Plain both ends |
| Hub Diameter: |
| 0.984 inches both ends |
| Material: |
| Steel comp e9310 |
| Material Specification: |
| Ams 6260 assn standard single material response |
| Style Designator: |
| Protruding hubs |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 3020-00-925-5698

Spur Gear - Page 2 of 2



Demilitarization:

No

Fiig:

A27300