## NSN 3020-00-929-1559

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-929-1559

Body Style:
Webbed, solid
Attachment Method:
Mounting hole
Pitch Diameter:
0.8000 inches
Teeth Quantity:
64
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
56 transversely through hub, first end
Mounting Hole Thread Size:
0.086 inches transversely through hub, first end
Mounting Hole Type And Quantity:
1 plain transversely through hub, first end
Outside Diameter:
0.825 inches
Nominallength:
0.275 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.125 inches second end
Face Width:
0.062 inches
Bore Diameter:
0.090 inches both ends
Hub Style Designator:
Plain second end
Hub Diameter:
0.218 inches first end
First Groove Width:
0.017 inches first end
First Groove Diameter:
0.203 inches first end
Distance From End To First Groove:

0.037 inches first end

## **NSN 3020-00-929-1559** Spur Gear - Page 2 of 2



Second Groove Width:
0.010 inches first end
Second Groove Diameter:
0.198 inches first end
Distance From End To Second Groove:
0.078 inches first end
Material:
Aluminum alloy
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625 military specification single treatment response
Style Designator:
Protruding hubs
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300
Mil-std (military Standard):
Mil-a-8625 spec.