NSN 3020-00-929-1559

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-929-1559

Body Style: Webbed, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 0.8000 inches **Teeth Quantity:** 64 **Bore Style:** Plain both ends Mounting Hole Thread Series Designator: Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 56 transversely through hub, first end Mounting Hole Thread Size: 0.086 inches transversely through hub, first end Mounting Hole Type And Quantity: 1 plain transversely through hub, first end **Outside Diameter:** 0.825 inches Nominallength: 0.275 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.125 inches second end Face Width: 0.062 inches **Bore Diameter:** 0.090 inches both ends Hub Style Designator: Plain second end **Hub Diameter:** 0.218 inches first end First Groove Width: 0.017 inches first end First Groove Diameter: 0.203 inches first end **Distance From End To First Groove:** 0.037 inches first end

NSN 3020-00-929-1559

Spur Gear - Page 2 of 2



Second Groove Width: 0.010 inches first end Second Groove Diameter: 0.198 inches first end **Distance From End To Second Groove:** 0.078 inches first end Material: Aluminum alloy Surface Treatment: Anodize **Surface Treatment Specification:** Mil-a-8625 military specification single treatment response Style Designator: Protruding hubs Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A27300 Mil-std (military Standard): Mil-a-8625 spec.