NSN 3020-00-933-6187

Sprocket Wheel - Page 1 of 2

Between 0.991 inches and 0.995 inches

Outside Diameter:



View Online at https://aerobasegroup.com/nsn/3020-00-933-6187

Overall Length:
0.343 inches
Thread Size:
0.114-40
Bore Diameter:
Between 0.1873 inches and 0.1878 inches
Bore Length:
0.343 inches
Pitch Diameter:
Between 0.941 inches and 0.943 inches
Securing Hole Quantity:
1
Furnished Items And Quantity:
Setscrew 1
Face Width:
0.125 inches
Design Form:
Plain
Bore Type:
Straight
Counterbore Feature:
Not included
Hole Location:
Centered 0.110 in. From end of hub
Keying Facility:
Not included
Securing Method:
Threaded hole
Lightening Hole:
Not included
Protruding Hub Characteristic:
Plain
Securing Location:
Aa end
Belt/chain/film Size For Which Designed:
Roller chain
Roller Chain Pitch Type For Which Designed:
Single pitch
Teeth Row Quantity:

NSN 3020-00-933-6187 Sprocket Wheel - Page 2 of 2



Teeth Quantity Per Row:
20
Hardness Rating Test Method:
Not rated
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
0.148 inches
Hub End Outside Diameter And Location:
0.375 inches aa end
Distance From Outside Flange/rim To Hub End And Location:
0.218 inches aa end
Material:
Steel, qq-s-764, type 303, cond a-canceled
Material:
Steel comp 303
Material Specification:
Qq-s-764, type 303, cond a-canceled federal specification single material response
Surface Treatment:
Passivate
Style Designator:
Plain
Surface Treatment:
Passivated
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
Т353-с