## NSN 3020-00-933-6884

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-933-6884 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: Between 1.9990 inches and 2.0000 inches **Teeth Quantity:** 160 **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 56 transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end Nominallength: 0.312 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.187 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 0.125 inches both ends **Hub Diameter:** 0.312 inches first end Material: Steel comp 303 **Material Specification:** Mil-s-7720, comp 303s military specification single material response **Surface Treatment: Passivate Style Designator:** Protruding hub Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

Yes - demil/mli

## NSN 3020-00-933-6884

Spur Gear - Page 2 of 2



Fiig:

A27300

Mil-std (military Standard):

Mil-s-7720 spec.