NSN 3020-00-933-6890

Spur Gear - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/3020-00-933-6890

| Plain, solid |
|----------------------------------------------------|
| Attachment Method: |
| Mounting hole |
| Pitch Diameter: |
| Between 0.8243 inches and 0.8250 inches |
| Teeth Quantity: |
| 33 |
| Bore Style: |
| 10a w/ keyway both ends |
| Backlash Designation: |
| Grade c |
| Mounting Hole Thread Series Designator: |
| Unc transversely through hub, first end |
| Mounting Hole Thready Qty Per Inch (tpi): |
| 32 transversely through hub, first end |
| Mounting Hole Thread Size: |
| 0.138 inches transversely through hub, first end |
| Mounting Hole Type And Quantity: |
| 1 threaded transversely through hub, first end |
| Outside Diameter: |
| 0.874 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 14.5000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.313 inches first end |
| Face Width: |
| 0.250 inches |
| Bore Diameter: |
| 0.312 inches both ends |
| Keyway Width: |
| 0.065 inches both ends |
| Distance From Bore Center To Keyway Bottom: |
| 0.196 inches both ends |
| Hub Style Designator: |
| Plain first end |
| Hub Diameter: |
| 0.625 inches first end |
| Precision Classification: |
| Quality number 12 |

NSN 3020-00-933-6890

Spur Gear - Page 2 of 2

Fiig: A27300



| Material: |
|--------------------------------------------------------------------------|
| Steel comp 303 |
| Material Specification: |
| Qq-s-764, type303, cond a federal specification single material response |
| Style Designator: |
| Protruding hub |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |