# NSN 3020-00-933-6890

Spur Gear - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/3020-00-933-6890



**Body Style:** 

Plain, solid

**Attachment Method:** 

Mounting hole

#### Pitch Diameter:

Between 0.8243 inches and 0.8250 inches

# **Teeth Quantity:**

33

#### Bore Style:

10a w/ keyway both ends

## **Backlash Designation:**

Grade c

#### Mounting Hole Thread Series Designator:

Unc transversely through hub, first end

#### Mounting Hole Thready Qty Per Inch (tpi):

32 transversely through hub, first end

#### Mounting Hole Thread Size:

0.138 inches transversely through hub, first end

# Mounting Hole Type And Quantity:

1 threaded transversely through hub, first end

# Outside Diameter:

0.874 inches

Tooth Form:

Standard

## Pressure Angle:

14.5000 degrees

## Distance Between Body Face And Protruding Hub End:

0.313 inches first end

#### Face Width:

0.250 inches

#### Bore Diameter:

0.312 inches both ends

#### Keyway Width:

0.065 inches both ends

## Distance From Bore Center To Keyway Bottom:

0.196 inches both ends

# Hub Style Designator:

Plain first end

# Hub Diameter:

0.625 inches first end

#### **Precision Classification:**

Quality number 12

# NSN 3020-00-933-6890

Spur Gear - Page 2 of 2



Material:

Steel comp 303

# Material Specification:

Qq-s-764, type303, cond a federal specification single material response

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

---

# Demilitarization:

No

# Fiig:

A27300