## NSN 3020-00-934-9093

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-934-9093

**Body Style:** Webbed, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 0.9375 inches **Teeth Quantity:** 30 **Bore Style:** W/counterbore counterbore, first end Hardness Rating: 32.0 rockwell c and 36.0 rockwell c Mounting Hole Type And Quantity: 2 plain transversely through hub, first end **Outside Diameter:** 0.997 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.252 inches first end **Distance Between Body Face And Recessed Hub End:** 0.031 inches second end Face Width: 0.186 inches **Bore Diameter:** 0.313 inches both ends **Counterbore Depth:** 0.252 inches counterbore, first end **Counterbore Diameter:** 0.422 inches counterbore, first end Hub Style Designator: Plain second end **Hub Diameter:** 0.692 inches first end First Groove Width: 0.032 inches first end First Groove Diameter: 0.655 inches first end **Distance From End To First Groove:** 

0.095 inches first end

# NSN 3020-00-934-9093

Spur Gear - Page 2 of 2



Mounting Hole Diameter:

0.126 inches transversely through hub, first end

## **Special Features:**

End of first hub chamfered 0.015 in. By 45 degs

Material:

Steel comp 4320

## Material Specification:

66 federal standard single material response

## Style Designator:

One protruding hub, one recessed hub

Shelf Life:

N/a

Unit Of Measure:

---

### Demilitarization:

No

### Fiig:

A27300