## NSN 3020-00-934-9633

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-934-9633

Body Style:

Webbed, offset, solid

**Attachment Method:** 

Mounting hole

Pitch Diameter:

0.4220 inches

Teeth Quantity:

27

Bore Style:

W/counterbore counter bore, second end

Mounting Hole Thread Series Designator:

Unc transversely through hub, first end

Mounting Hole Thread Size:

0.112 inches transversely through hub, first end

### Mounting Hole Type And Quantity:

1 threaded transversely through hub, first end

**Outside Diameter:** 

0.451 inches

**Tooth Form:** 

Stub

Pressure Angle:

20.0000 degrees

#### **Distance Between Body Face And Protruding Hub End:**

0.155 inches first end

**Body Recess Depth:** 

0.031 inches second end

Face Width:

0.047 inches

Bore Diameter:

0.187 inches both ends

**Counterbore Depth:** 

0.031 inches counter bore, second end

#### Counterbore Diameter:

0.328 inches counter bore, second end

Hub Style Designator:

Plain first end

Hub Diameter:

0.367 inches first end

**Special Features:** 

One 0.020 in. Dia. Hole on face of gear 0.148 in. From ctr of hole to ctr of bore

Material:

Steel comp 416

# NSN 3020-00-934-9633

Spur Gear - Page 2 of 2



Material Specification:

66 assn standard single material response

Surface Treatment:

Oxide

Style Designator:

Protruding hub, recessed body

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300