NSN 3020-00-936-5735

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-936-5735 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 0.4167 inches **Teeth Quantity:** 40 **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 40 transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 0.435 inches Nominallength: 0.312 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.187 inches first end Face Width: 0.125 inches **Bore Diameter:** 0.187 inches both ends **Hub Diameter:** 0.310 inches first end **Precision Classification:** Quality number 10 or quality number 11 Material: Steel comp 416 **Material Specification:** Qq-s-763, class416 federal specification single material response **Surface Treatment: Passivate Style Designator:** Protruding hub

N/a

Shelf Life:

NSN 3020-00-936-5735

Spur Gear - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|-----|-----|------|
| In | 18 | <i>(</i>)+ | МЛО | 201 | ure: |
| | | | | | |

--

Demilitarization:

Yes - demil/mli

Fiig:

A27300