NSN 3020-00-936-5736

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-936-5736

Body Style: Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 1.2708 inches **Teeth Quantity:** 122 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 40 transversely through hub, first end **Mounting Hole Thread Size:** 0.112 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 1.289 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.187 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 0.187 inches both ends **Hub Style Designator:** Plain first end **Hub Diameter:** 0.370 inches first end **Precision Classification:** Quality number 10 or quality number 11 Material: Steel comp 416

Material Specification:

Qq-s-763, class416 federal specification single material response

Surface Treatment:

Passivate

NSN 3020-00-936-5736

Spur Gear - Page 2 of 2



Sty	16	u	=5	ıu	 aı	u	ч.	_

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A27300