NSN 3020-00-936-8490

Sprocket Wheel - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/3020-00-936-8490



Outside Diameter:

1.490 inches

Overall Length:

1.250 inches

Bore Diameter:

Between 0.7485 inches and 0.7495 inches

Bore Length:

1.250 inches

Drilled Hole Diameter:

Any acceptable

Pitch Diameter:

1.361 inches

Securing Hole Quantity:

2

Face Width:

0.359 inches

Guide:

Not included

Design Form:

Plain

Bore Type:

Straight

Counterbore Feature:

Not included

Hole Location:

One hole drilled through hub, 0.400 in. From hub end

Keying Facility:

Not included

Securing Method:

Drilled hole

Lightening Hole:

Not included

Protruding Hub Characteristic:

Plain

Securing Location:

Aa end

Err Default:

Err default

Belt/chain/film Size For Which Designed:

Roller chain

Roller Chain Pitch Type For Which Designed:

Single pitch

NSN 3020-00-936-8490 Sprocket Wheel - Page 2 of 2



| Teeth Row Quantity: |
|---|
| 2 |
| Center To Center Distance Between Teeth Rows: |
| 0.252 inches |
| Teeth Quantity Per Row: |
| 17 |
| Asa Standard Chain Number: |
| 25-2 |
| Hardness Rating Test Method: |
| Not rated |
| Bore Bearing: |
| Not included |
| Hub External Keyway: |
| Not included |
| Tooth Pitch: |
| 0.250 inches |
| Hub End Outside Diameter And Location: |
| 1.047 inches aa end |
| Distance From Outside Flange/rim To Hub End And Location: |
| 0.891 inches both ends |
| Material: |
| Steel |
| Material: |
| Steel |
| Surface Treatment: |
| Cadmium |
| Style Designator: |
| Plain |
| Surface Treatment: |
| Cadmium plated |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

Т353-с