NSN 3020-00-937-1413

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-937-1413 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 3.9375 inches **Teeth Quantity:** 63 **Bore Style:** W/counterbore both ends **Backlash Designation:** Grade c **Mounting Hole Thread Series Designator:** Unf axially through body, first end Mounting Hole Thready Qty Per Inch (tpi): 24 axially through body, first end **Mounting Hole Type And Quantity:** 6 threaded axially through body, first end Nominallength: 4.750 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Face Width:** 1.130 inches **Bore Diameter:** 0.250 inches both ends **Counterbore Diameter:** 1.000 inches second end **Precision Classification:** Quality number 9 **Special Features:** 2nd counterbore on 2nd end 0.380 in.Dia, 2.812 in.Deep; thd on longest hub end, 0.781-32 uns Material: Steel comp 4130 **Material Specification:**

Mil-s-6758 military specification single material response

Style Designator:

Protruding hubs

Shelf Life:

N/a

NSN 3020-00-937-1413

Spur Gear - Page 2 of 2



П	Init	7 1+	Measure:
u	,,,,,	v	wicasuic.

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-s-6758 spec.