

View Online at <https://aerobasegroup.com/nsn/3020-00-938-0960>

Counterbore Diameter:

Between 1.880 inches and 1.198 inches

Counterbore Depth:

Between 0.131 inches and 0.140 inches

Groove Depth:

0.156 inches

Groove Width:

0.150 inches

Outside Diameter:

5.218 inches

Bore Diameter:

1.437 inches

Bore Length:

0.479 inches

Pitch Diameter:

4.906 inches

Groove Radius:

0.050 inches

Material And Location:

Aluminum alloy, qq-a-355-canceled

Face Width:

0.750 inches

Design Form:

Plain

Bore Type:

Straight

Bearings:

Included

Groove Quantity:

2

Counterbore Feature:

Included

Bearing Quantity:

1

Counterbore Location:

Aa end or bb end

Keying Facility:

Not included

Split Hub Feature:

Not included

Lightening Hole:

Not included

Integral Cooling Vane:

Not included

Groove Shape:

U

Bore Feature:

Included

Bearing Type:

Ball

Special Features:

Drilled hole on face of pulley through, 0.256 maximum in. Diameter with counterbore 0.750 in. Diameter 0.180 in. Dp, located 1.500 in. Above cntr of bore to left of cables passing through face which stop pulley; holes for cables are 0.271 in. Diameter at surface and 0.157 in.

Diameter at bottom; cable holes intersect at 120 degree angle from each other on a chord 1.750 in. From cntr of bore

Style Designator:

Plain

Supplementary Features:

Differs from -039 because -029 is right handed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T353-a