

View Online at <https://aerobasegroup.com/nsn/3020-00-938-0961>

**Counterbore Diameter:**

Between 1.880 inches and 1.198 inches

**Counterbore Depth:**

Between 0.131 inches and 0.140 inches

**Groove Depth:**

0.156 inches

**Groove Width:**

0.150 inches

**Outside Diameter:**

5.218 inches

**Bore Diameter:**

1.437 inches

**Bore Length:**

0.479 inches

**Pitch Diameter:**

4.906 inches

**Groove Radius:**

0.050 inches

**Material And Location:**

Aluminum alloy, qq-a-355-canceled

**Face Width:**

0.750 inches

**Design Form:**

Plain

**Bore Type:**

Straight

**Bearings:**

Included

**Groove Quantity:**

2

**Counterbore Feature:**

Included

**Bearing Quantity:**

1

**Counterbore Location:**

Aa end or bb end

**Keying Facility:**

Not included

**Split Hub Feature:**

Not included

**Lightening Hole:**

Not included

**Integral Cooling Vane:**

Not included

**Groove Shape:**

U

**Bore Feature:**

Included

**Bearing Type:**

Ball

**Special Features:**

Drilled hole on face of pulley through, 0.256 maximum in. Diameter with counterbore 0.750 in. Diameter 0.180 in. Dp, located 1.500 in. Below cntr of bore to right of cables passing through face which stops pulley; holes for cables are 0.271 in. Diameter at surface and 0.157 in. Diameter at bottom; cable holes intersect at 120 degree angle from each other on a chord 1.750 in. From cntr of bore

**Style Designator:**

Plain

**Supplementary Features:**

Differs from -029 because -039 is left handed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T353-a