NSN 3020-00-940-9473

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-940-9473

Body Style:
Webbed, solid
Attachment Method:
Mounting hole
End Application:
ARMA-ME-NTS-UBSY
Pitch Diameter:
1.3125 inches
Teeth Quantity:
42
Bore Style:
Plain both ends
Backlash Designation:
Grade c
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Hardness Rating:
36.0 rockwell c and 42.0 rockwell c
Mounting Hole Thread Size:
0.138 inches transversely through hub, first end
Mounting Hole Type And Quantity:
1 plain transversely through hub, first end and 1 threaded transversely through hub, first end
Outside Diameter:
1.375 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Face Width:
0.265 inches
Bore Diameter:
0.375 inches both ends
olor o monoc boar ondo
Hub Style Designator:
Hub Style Designator:
Hub Style Designator: Pinned first end
Hub Style Designator: Pinned first end Hub Diameter:
Hub Style Designator: Pinned first end Hub Diameter: 0.562 inches first end
Hub Style Designator: Pinned first end Hub Diameter: 0.562 inches first end Precision Classification:
Hub Style Designator: Pinned first end Hub Diameter: 0.562 inches first end Precision Classification: Quality number 9

Steel

NSN 3020-00-940-9473

Spur Gear - Page 2 of 2



Surface	I reatment
Passivate	9

Style Designator:

Protruding hub, recessed body

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300