# NSN 3020-00-941-0270

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-941-0270

View Online at https://aerobasegroup.com/nsn/3020-00-94
Outside Diameter:
1.136 inches
Overall Length:
0.280 inches
Bore Diameter:
0.250 inches
Bore Length:
0.280 inches
Drilled Hole Diameter:
Between 0.062 inches and 0.065 inches
Securing Hole Quantity:
8
Face Width:
0.125 inches
Design Form:
Plain
Bore Type:
Straight
Counterbore Feature:
Not included
Hole Location:
Perpendicular to bore through hub
Keying Facility:
Not included
Securing Method:
Drilled hole
Lightening Hole:
Not included
Protruding Hub Characteristic:
Plain
Securing Location:
Aa end
Teeth Quantity Per Row:
10
Hardness Rating Test Method:
Not rated
Bore Bearing:
Not included
Hub External Keyway:
Not included
Hub End Outside Diameter And Location:

0.500 inches aa end

## NSN 3020-00-941-0270

Sprocket Wheel - Page 2 of 2



## Distance From Outside Flange/rim To Hub End And Location:

0.155 inches aa end

## Material:

Steel, qq-s-763, class 303, cond a

#### Material:

Steel comp 303

## Material Specification:

Qq-s-763, class 303, cond a federal specification single material response

#### Surface Treatment:

Passivate

#### Style Designator:

Plain

## Surface Treatment:

Passivated, mil-f-14072, e300

#### Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

## Fiig:

Т353-с