## NSN 3020-00-941-2989

Spur Gear - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/3020-00-941-2989

#### **Body Style:**

Plain, solid

## **Attachment Method:**

Clamp

## **Pitch Diameter:**

Between 0.9365 inches and 0.93675 inches

## **Teeth Quantity:**

60

Bore Style:

Plain both ends

## **Backlash Designation:**

Grade c

#### Outside Diameter:

0.968 inches

#### **Tooth Form:**

Standard

## Pressure Angle:

20.0000 degrees

## Distance Between Body Face And Protruding Hub End:

0.250 inches first end

## Face Width:

0.125 inches

## Bore Diameter:

0.125 inches both ends

#### Hub Style Designator:

Split first end

#### Hub Diameter:

0.187 inches first end

## Clamping Surface Length:

0.250 inches first end

#### **Precision Classification:**

Quality number 10

#### Material:

Aluminum alloy 2024

## **Material Specification:**

Qq-a-225/6, t4 federal specification single material response

## Surface Treatment:

Anodize hub

## Surface Treatment Specification:

Mil-a-8624, type 1 military specification single treatment response body

## Style Designator:

Protruding hub



# NSN 3020-00-941-2989

Spur Gear - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A27300

## Mil-std (military Standard):

Mil-a-8625 spec.

