NSN 3020-00-941-6015

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-941-6015

·
Body Style:
Plain, with lightening holes
Attachment Method:
Mounting hole
Pitch Diameter:
3.1875 inches
Teeth Quantity:
102
Bore Style:
Plain both ends
Backlash Designation:
Grade c
Mounting Hole Thread Series Designator:
Unc axially through body, first end
Mounting Hole Thready Qty Per Inch (tpi):
40 axially through body, first end
Mounting Hole Thread Size:
0.112 inches axially through body, first end
Mounting Hole Type And Quantity:
3 threaded axially through body, first end
Outside Diameter:
3.250 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.175 inches first end
Face Width:
0.125 inches
Bore Diameter:
0.188 inches both ends
Hub Style Designator:
1 step first end
End Length:
0.062 inches first end
Precision Classification:
Quality number 10 or quality number 11
End Diameter:
0.250 inches first end
First Step Length:

0.113 inches first end

NSN 3020-00-941-6015

Spur Gear - Page 2 of 2

A27300



First Step Diameter:
0.375 inches first end
Bolt Hole Circle Diameter:
2.000 inches axially through body, first end
Special Features:
Mtg holes spaced 120 degrees apart
Material:
Copper alloy 675
Material Specification:
Qq-b-728, class a, comp hard /d/ federal specification single material response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig: