NSN 3020-00-941-6118

Spur Gear - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/3020-00-941-6118

Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
0.5625 inches
Teeth Quantity:
27
Bore Style:
Plain both ends
Backlash Designation:
Grade c
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
32 transversely through hub, first end
Mounting Hole Thread Size:
0.138 inches transversely through hub, first end
Mounting Hole Type And Quantity:
2 threaded transversely through hub, first end
Outside Diameter:
0.604 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.250 inches first end
Face Width:
0.125 inches
Bore Diameter:
0.250 inches both ends
Hub Style Designator:
Plain first end
Hub Diameter:
0.500 inches first end
Special Features:
Mtg holes spaced 90 degrees apart 0.125 in. From end of hub
Material:
Steel comp 303
Material Specification:
Qq-s-764, type 303, cond a federal specification single material response

NSN 3020-00-941-6118

Spur Gear - Page 2 of 2



$\overline{}$			-			
~ I	ırfa	ഫ	ırc	natr	nΔn	

Passivate

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300