## NSN 3020-00-941-7480

View Online at https://aerobasegroup.com/nsn/3020-00-941-7480

Spur Gear - Page 1 of 2



**Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 0.9000 inches **Teeth Quantity:** 108 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 56 transversely through hub, first end **Mounting Hole Thread Size:** 0.086 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 2 threaded transversely through hub, first end **Outside Diameter:** 0.916 inches Nominallength: 0.210 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.150 inches first end **Face Width:** 0.060 inches **Bore Diameter:** 0.125 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.310 inches first end **Precision Classification:** Quality number 12 Material: Steel comp 303se **Material Specification:** Mil-s-7720, comp 303se military specification single material response

## NSN 3020-00-941-7480

Spur Gear - Page 2 of 2



Passivate
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:

Mil-std (military Standard):

Mil-s-7720 spec.

**Surface Treatment:**