# NSN 3020-00-943-7465

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-943-7465

# **Body Style:**

Plain, solid

# **Pitch Diameter:**

Between 1.0406 inches and 1.0416 inches

# Teeth Quantity:

50

# Bore Style:

Plain both ends

# **Backlash Designation:**

Grade c

# **Outside Diameter:**

1.082 inches

# Tooth Form:

Standard

#### Pressure Angle:

20.0000 degrees

# Distance Between Body Face And Protruding Hub End:

0.202 inches first end

#### Face Width:

0.093 inches

# Bore Diameter:

0.187 inches both ends

# Hub Style Designator:

Pinned first end

# Hub Diameter:

0.375 inches first end

# **Precision Classification:**

Quality number 10 or quality number 11

# Material:

Aluminum alloy 6061

# **Material Specification:**

Qq-a-225/8, t6 federal specification single material response

# Surface Treatment:

Anodize

# Surface Treatment Specification:

Mil-a-8625, type 1 military specification single treatment response

# Style Designator:

Protruding hub

# **Furnished Items And Quantity:**

1 setscrew

# Shelf Life:

N/a

# NSN 3020-00-943-7465

Spur Gear - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.

